


CARNet Users Conference 2002


How to make most of your Linux workplace?

Vlatko Košturjak
kost@linux.hr




How to take most of any workplace?

- Powerful
- Easy
- User friendly
- Cutting-edge
- Well organized




Linux?

- *Clone of UNIX*
 - *invented at AT&T in the 60's*
 - *UNIX forked significantly into a number of proprietary products (SunOS, AIX, etc)*
- *multi-user*
- *multi-process networking operating system*
- *open source*
 - *active development*
 - *open*
 - *free*
 - *secure*




Linux and workplace?

Which operating system family do you personally consider most appropriate for a workplace desktop?




<http://www.misterpoll.com>

- *“If a user follows simple philosophy and logic which lies behind, Linux can be used as a very good and productive workplace. “ -workshop abstract*




Kernel / distributions

- Kernel
 - the core of the system
 - written by Linus Torvalds, now it is written by thousands of developers
- Distributions
 - consist of
 - GNU software from FSF
 - kernel, installer, ...
 - RedHat, Suse, Debian, Mandrake, ...
 - Linux Standard Base




Everything is a file


- everything really means everything
 - serial port
 - hard disk
 - cd rom
 - partition on a hard disk
 - ethernet card
 - sound card
 - ...
 - directories




Small tools doing small jobs


- Linux comes with a lot of small programs called “tools”
- each tool is generally capable of performing a very simple and specific task
- specific tool = powerful tool
- Examples: sort, wc, grep, ...






Organization of the File Tree






File systems / Mount points


- mount points = directories







X

- a portable, network-transparent window system
- correct names
 - X
 - X Window System
 - X Version 11
 - X Window System, Version 11
 - X11





X Architecture







Client-Server architecture





X architecture] [





Window managers and libraries


Libraries

GTK
QT
FLTK
Motif
TK
...

Window Managers

Twm
Olwm
IceWM
Qvwm
Window Maker
Xfce
Enlightment
Synapse
...


KDE
GNOME



KDE




- powerful open source graphical desktop environment for Unix workstations
- *combines ease of use, contemporary functionality, and outstanding graphical design with the technological superiority of the Unix operating system*
- *Internet project that is truly open in every sense*
 - *use, modify, learn, redistribute, ...*
- *includes powerful document technology*
- *mature desktop suite*



GNOME




- an effort to create an entirely free desktop environment for free systems
- main objective is to provide a user friendly suite of applications and an easy-to-use desktop
 - the objectives of the project have been extended to address a number of problems in the existing Unix infrastructure
- project acts as an umbrella, the major components of GNOME are:
 - The GNOME desktop
 - The GNOME development platform
 - The GNOME Office



Process control


- all processes are organized in the form of tree
 - the root of this tree is init
- each process has a number (Process ID = PID) and a number of its parent process (Parent Process ID = PPID)
- every process in Unix can react to signals sent to it
 - there are 64 different signals
 - process can define its own behaviour for each signal (except for signal number 9 and 19)



Process control II


The screenshot shows the 'Process Table - KDE System Guard' window. The 'Process Table' tab is active, displaying a list of running processes on the 'localhost'. The table has columns for Name, PID, User%, System%, Nice, and VmSize. The processes listed include ksysguard, X, ksysguardd, ksnapshot, init, keventd, kapmd, ksoftirqd_CPU0, kswapd, bdflush, kupdated, mdrecoveryd, kjournald, devfsd, and several other instances of kjournald.

Name	PID	User%	System%	Nice	VmSize
ksysguard	8715	3.55	0.00	0	23160
X	3164	2.03	2.54	-10	306408
ksysguardd	8716	1.52	1.02	0	1628
ksnapshot	8718	1.02	0.00	0	23124
init	1	0.00	0.00	0	1412
keventd	2	0.00	0.00	0	0
kapmd	3	0.00	0.00	0	0
ksoftirqd_CPU0	4	0.00	0.00	19	0
kswapd	5	0.00	0.00	0	0
bdflush	6	0.00	0.00	0	0
kupdated	7	0.00	0.00	0	0
mdrecoveryd	8	0.00	0.00	-20	0
kjournald	12	0.00	0.00	0	0
devfsd	65	0.00	0.00	0	1780
kjournald	272	0.00	0.00	0	0
kjournald	273	0.00	0.00	0	0
kjournald	274	0.00	0.00	0	0




/proc filesystem

- virtual filesystem
- it takes no room on your disk
- way to obtain information on the system
 - system state, processes, hardware, ...
- way to change some kernel parameters in real time




/proc filesystem - processes

- /proc/process_id/ directory holds info about each process on the system
 - cmdline
 - cwd
 - environ
 - exe
 - fd
 - maps
 - root
 - status




/proc - hardware/kernel

- proc contains a lot of information on the hardware and kernel
 - apm
 - cpuinfo
 - filesystems
 - interrupts
 - ioports
 - dma
 - meminfo
 - bus




/proc - kernel configuration

- /proc/sys subdirectory
 - setting different kernel parameters
 - /proc/sys/net/ipv4/ip_forward
 - /proc/sys/net/ipv4/icmp_echo_ignore_all
 - /proc/sys/net/ipv4/conf/all/rp_filter
 - /proc/sys/net/ipv4/ip_default_ttl
 - /proc/sys/fs/file-max
 - /proc/sys/fs/inode-max




Linux startup

- unix startup schemes
 - BSD
 - System V
- kernel executes `/sbin/init` after kernel startup
- `init`
 - the father of all processes on the system
 - configuration file: `/etc/inittab`
 - responsible for taking the system to the desired runlevel



Linux startup - runlevels

- 7 runlevels
 - 0 machine stop
 - 1 single-user mode
 - 2 multi-user mode (no networking)
 - 3 multi-user mode
 - 4 unused
 - 5 multi-user mode with GUI
 - 6 restart
- /etc/rc.d/
 - rc.sysinit
 - rc.local



Killing “bad” applications

- xkill = CTRL+ALT+ESC

kap@desktop - KPM

cpu [bar] mem [bar] swap (none)

user [bar] nice [bar] sys [bar] idle [bar] used [bar] buff [bar] cach [bar] free [bar]

up 18:10

PID	USER	PRI	NICE	SIZE	RSS	SHARE	STAT	%CPU	%MEM	TIME	CMDLINE
8718	vkosturj	12	0	12992	12992	8868	S	3,70	10,25	1.24s	ksnapshot -icon ksnapst
8715	vkosturj	15	0	13052	13052	8480	S	4,48	10,30	4.69s	ksysguard
8717	vkosturj	15	0	10928	10928	7032	R	1,56	8,62	2.26s	kpm -icon kpm.png -mini
8716	vkosturj	13	0	772	772	568	S	3,51	0,61	3.46s	ksysguardd
3164	root	8	-10	294228	13464	5564	S<	2,34	10,59	10.41	/etc/X11/X -deferglyphs
8720	vkosturj	9	0	7788	5072	4716	S	0,00	4,00	0.09s	kdeinit: kio_file file /tmp/
3486	vkosturj	9	0	8880	5508	4280	S	0,00	4,35	0.26	kdeinit: kicker
5	root	9	0	0	0	0	SW	0,00	0,00	0.11	(kswapd)
8714	vkosturj	9	0	8136	4084	2068	S	0,19	3,22	0.24s	xmms
3481	vkosturj	9	0	6244	3172	2448	S	0,19	2,50	0.13	kdeinit: kwin
8713	vkosturj	9	0	8136	4084	2068	S	0,00	3,22	0.14s	xmms
2936	xfz	9	0	12152	3940	3308	S	0,00	3,11	0.13	xfz -port -1 -daemon -dr
3990	vkosturj	9	0	30816	17172	8092	S	0,00	13,55	18.53	/usr/bin/galeon-bin
3583	vkosturj	9	0	30776	23840	19524	S	0,00	18,81	9.03	/opt/OpenOffice.org1.0/


Tom Guard

System Load | Process Table

localhost: Running Processes


Name	PID	User%	System%	Nice	VmSize
ksysguard	8715	3.55	0.00	0	23160
X	3164	2.03	2.54	-10	306408
ksysguardd	8716	1.52	1.02	0	1628
ksnapshot	8718	1.02	0.00	0	23124
init	1	0.00	0.00	0	1412
keventd	2	0.00	0.00	0	0
kapmd	3	0.00	0.00	0	0
ksoftirqd_CPU0	4	0.00	0.00	19	0
kswapd	5	0.00	0.00	0	0
bdfush	6	0.00	0.00	0	0
kupdated	7	0.00	0.00	0	0
mdrecoveryd	8	0.00	0.00	-20	0
kjournald	12	0.00	0.00	0	0
devfsd	65	0.00	0.00	0	1780
kjournald	272	0.00	0.00	0	0
kjournald	273	0.00	0.00	0	0
kjournald	274	0.00	0.00	0	0

Tree | All processes | Pause | Refresh | Kill




System freeze

- under X (GUI)
 - ctrl-alt-backspace - X shutdown
 - login from network
 - switch to other console (ctrl+alt+f1, ctrl+alt+f2, ...)
- System Request (SysRq)
 - raw mode LALT+SysRq+r
 - sync disk LALT+SysRq+s
 - killall ps LALT+SysRq+e
 - read-only LALT+SysRq+u
 - reboot LALT+SysRq+b



Command line

- terminals
 - xterm, rxvt, gterm, eterm, ...
- used for sending direct commands to the system
- extremely powerful
 - command line completion
 - history
 - organization of jobs
 - synergy of tools
- “*Command line is your friend!*” © Dobrica



Commands

dir

ls

cd

cd

cd..

cd ..

type

cat

less

move

mv

copy


cp

del

rm

md

mkdir



Shell globbing patterns

- which files match the specific pattern
- *.txt matches all files with names ending with .txt
- matching is done with shell itself

ls *.txt


ls

*.txt

ls

letter.txt phones.txt todo.txt





Shell globbing patterns][

? matches one and only one character


* matches zero or more characters

[...] matches any character found in the []

[!...] matches any character not found in
the []

{p1,p2} matches p1 or p2 where p1 and p2 are
also globbing patterns

Examples: documents/cuc[0-9]/*.doc



Command line tips

- redirections

- > `ls *.doc > dokumenti.txt`

- `ls *.txt >> dokumenti.txt`


- < `gzip -dc < dokument.txt.gz`

- `mysql baza < create.sql`

- pipe


- | `who | wc -l`

“the most quoted pipe in the world”




Regular expression (regexp)

- A regular expression describes strings of characters.
- It's a pattern that matches certain strings and doesn't match others.
- Programs that use regexp
 - grep, sed, awk, ed, vi, emacs, ...
 - each program has a different set of (mostly overlapping) template characters
- Typical example: **a.*c.*d**



Regular expression explanation

- * matches zero or more characters
- + matches one or more characters
- ? matches zero or one character
- . matches any character except newline ($\backslash n$)
- [ab] matches any character found in the []
- [^ab] matches any character not found in the []
- x{min,max}



Regular expression examples


`.*changed.*permission`

`grep '.*changed.*permission' /var/log/syslog`

`grep 'changed.*permission.*to [4]?[67]' syslog`


`grep '.*changed.*' syslog | sed -e 's/changed/modified/g'`

`From.*spam@spam\.host\..*`




Optimizing Linux workplace

- speed
 - hdparm
 - services
- memory managment
 - services
- power managment
 - apm
 - hdparm



Future

- *“The idea that occurred to me was to work on unifying theme definitions, so that a user can define a theme just once and have it work with both GNOME and KDE.” -Richard Stallman*
- *Uniform themes (GNOME and KDE)*
- *Default Linux theme (look'n'feel)*




Interesting Quote

"A good deal of writing addicts need only a typewriter: I'm not interested in hda, hdb, hdz or anything else concerning technicalities and machine work! I just want to write 'chicken', if I feel like to. I want to see the word 'chicken' on the screen, and to have it printed out by a printer. Nothing else. Some of You skillful folks could make such a program which would, probably, have a wider commercial value. I repeat: just a typewriter, not an ICBM launcher or something."

Original text (on croatian):

"Jednom dobrom dijelu skribomana potrebna je isključivo pisaća mašina: ne interesira me hda, hdb, hdz, ni bilo što drugo što se tiče tehnike i rada mašine! Želim isključivo napisati 'kokoš' ako mi to padne napamet. Želim da riječ 'kokoš' vidim na monitoru, te da mi riječ 'kokoš' isprinta printer. Ništa drugo. Netko od Vas spretnijih bi mogao napraviti takav program, koji bi vjerojatno imao širu komercijalnu vrijednost. Ponavljam: samo pisaća mašina, ne i lanser za interkontinentalne rakete i slično."



Questions?

Vlatko Košturjak

E-mail:

kost@linux.hr